



65

χρόνια

σεβασμό στον μάστορα

δομικά υλικά

construction materials

Technical Data Sheet

Date: 13/06/2013

Edition Number: 4th

Atlacoll GLU

High-performance methylcellulose wallpaper adhesive, easy to apply and resistant to stains.



Description

Atlacoll GLU is a wallpaper adhesive made from methylcellulose for standard wallpapers. It is easy to apply, high-performing, and dries without staining. It can also be mixed with filler for spatula finishes.

Key Features

- High performance
 - Dries without stains
 - Covers up to 8 rolls
 - Easy to apply
 - Neutral and durable
- Suitable for application with brush, roller, or spatula
- Can be mixed with filler for spatula finishes

Preparation of Adhesive

1. Pour clean, cold water into a clean bucket according to the table below.
2. Stir the water vigorously and gradually add Atlacoll GLU while stirring.
3. Continue stirring until a homogeneous mixture forms.
4. Let the mixture rest for approximately 20 minutes, then stir again vigorously.

The adhesive is now ready for use.

Surface Preparation

The surface must be solid, clean, dry, and smooth. Thoroughly clean the substrate by removing any old wallpaper, loose paint, and adhesive residues. For highly absorbent walls, apply a primer according to the table below

Wallpaper Application

1. Apply the adhesive evenly on the back of the wallpaper using a clean and suitable brush.
2. Fold the wallpaper and, if necessary, roll it up.
3. Respect the soaking time indicated by the wallpaper manufacturer.
4. Adhere the wallpaper according to the manufacturer's instructions.

Important Instructions

- Immediately remove adhesive residues from the top of the wallpaper with a damp cloth.
- Clean your tools and bucket with warm water after use.



65

χρόνια

σεβασμό στον μάστορα

δομικά υλικά

construction materials

Atlacoll GLU

Technical Data Sheet

Date: 13/06/2013

Edition Number: 4th

Storage

Seal the Atlacoll GLU container tightly and store it in a cool, dry place.

Packaging

125 gr.

Usage and Coverage

| Application | Liters of Water | Coverage |
|---------------------|-----------------|-----------------------------------|
| Priming | 10 | Approximately 75 m ² . |
| Light Wallpapers | 8¾ | 10 rolls |
| Standard Wallpapers | 7½ | 8 rolls |
| Heavy Wallpapers | 6¼ | 6 rolls |

Safety Guidelines

Read the label before use. For detailed instructions and precautions, consult the product's Safety Data Sheet. Poison Control Center Telephone: +30 210 77 93 777.

